

## **CC15** Service Hose Crimper



### ENGINEERED TO ACCOMMODATE YOUR NEEDS

- Hose capacity 5/8" 1-2 wire and 1/2" 4SP.
- · Maximum head opening w/o dies 3.7" (94mm).
- Metric dial micrometer makes precise settings of crimp diameters simple.
- Built-in adjustable retraction stop limits ram retraction to only the amount required to remove the hose and coupling saving time on multiple crimps.
- Easy die removal (by hand) with dovetailed dies.
- Easy grease maintenance through the 8 grease fittings.
- · Start / Close push button or pneumatic pendent switch can be operated with hand or foot.
- Protective master die foam pads between the die fingers prevent debris from dropping into the critical surfaces and causing permanent damage.
- · Base mounting holes allow the crimper to be bench or truck bed mounted if required.

### DURABLE + RELIABLE DESIGN = PROFITABILITY

- · 33 Tons of crimping force.
- Small and quick acting crimping head.
- Complete range of dies and accessories available.



Max. Head Opening W/O Dies



Metric Dial Micrometer



Hold/Release valve: Permits the operator to jog and hold the dies in and position during setup.



Save Time: Manual Back Stop for multiple crimps of the same hose and fitting.



# **CUSTOM CRIMP**

Innovating SMART Hose Assembly Solutions Since 1979

### **CC15** Service Hose Crimper



(Included) Metric Dial Micrometer P/N:102941-600



(Included) Pneumatic Pendent Switch P/N:101349



(Included) Manual Back Stop P/N:103907



(Included) 8 Protective Master Die Foam Pads P/N:103285



(Included) CRIMPX Lubricant Grease 3 oz mini grease tube P/N:103887 and grease nipple



(Optional) Mini Grease Gun P/N:103889

The 1 HP motor delivers the power needed to get the job done quickly

Metric Dial Micrometer



Electrical Enclosure

Power Switch

Close push button

Hold / Release manual valve

**Power Cord** 

Voltage Tag

Oil level sight glass

Pneumatic Switch can be used with hands or feet

Small Footprint for minimum use of space

#### **CC15 Technical Specifications**

Crimping Force: 33 Ton

Hydraulic Hose Capacity: 5/8" 2 Wire 1/2" 4SP

Crimper Size: L: 16" x W: 23" x H: 19"

Crimper Weight: 150 lbs

Power: 1HP / 110V / 1Phase (Standard) 2HP / 220V / 1Phase (Optional) 1HP / 12V / 1Phase (Optional) 1HP / 24V / 1Phase (Optional)

Die series: K16

Adjustability: Manual / Metric

Opening w/o dies: 94mm / 3.7"

Master die travel: 27.5mm / 1.1"

Reservoir capacity: 13 Quarts

Oil type: ISO 46 Hydraulic Oil























